



Qualified Nozzles with Pressure Ranges (PSI)

Manufacturer	Nozzle Type	Size	Pressure		Pressure Range (PSI)																							
			Min	Max	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120	
ABJ Agri	ABJ	110.04	40	40																								
		110.06	40	40																								
AlbuZ	AVI	110025	40	80																								
		11003	40	70																								
		11004	40	70																								
		11005	40	65																								
		11006	40	60																								
Greeneye Technology	GEE	25-03	20	80																								
Greenleaf	AM	11003	15	35																								
		11004	15	35																								
		11005	15	35																								
		11006	15	35																								
	TADF	025	20	45																								
		03	20	40																								
		04	20	50																								
		05	20	60																								
		06	20	60																								
		08	20	60																								
	TDXL	11003	30	40																								
		11004	30	45																								
		11005	30	65																								
		11006	30	75																								
	TDXL-D	11002-D	30	65																								
		110025-D	30	70																								
		11003-D	30	90																								
		11004-D	30	90																								
		11005-D	30	85																								
11006-D		30	100																									
11008-D		30	80																									
SD	110-04	20	90																									
	110-05	20	85																									
	110-06	20	40																									
	110-08	20	80																									
	110-10	20	80																									
HyPro	TRD	80-03	20	55																								
		80-04	20	50																								
		80-05	20	55																								
		80-06	20	75																								
	ULD	120-03	20	30																								
		120-04	20	80																								
		120-05	20	70																								
		120-06	20	65																								
		120-08	20	40																								
	ULDM	130-03	30	80																								
130-04		30	80																									
130-05		30	100																									
130-06		30	100																									
130-08		30	100																									

For PWM Systems:

- NOZZLE** (orange box) Designed for use with PWM systems
- NOZZLE** (green box) Use with John Deere ExactApply™ system ONLY

Coverage guide (factor of type, size and/or pressure range):

- Provides best balance of coverage and drift control
- Provides additional drift control by creating larger droplets
- No classification

Manufacturer	Nozzle Type	Size	Pressure		Pressure Range (PSI)																								
			Min	Max	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120		
John Deere	PSTSL	6005-R4	20	80																									
		8005-R4	20	80																									
		8006-R4	30	75																									
	PSULD/ PSULDQ	2003	20	35																									
		2004	20	70																									
		2005	20	65																									
		2006	20	50																									
		2008	20	40																									
	PSULDM/ PSULDMQ	3003	30	80																									
		3004	30	80																									
		3005	30	100																									
		3006	30	100																									
		3008	30	100																									
	PSLDM/ PSLDMQ	2006	20	55																									
		2008	20	60																									
2010		20	45																										
Lechler	ID	120-04	20	80																									
		120-05	20	80																									
TeeJet	AI	65-02E	30	70																									
		65-025E	30	70																									
		65-03E	30	75																									
		65-04E	30	80																									
		65-05E	30	80																									
		65-06E	30	80																									
		80-02	30	65																									
		80-025	30	75																									
		80-03	30	75																									
		80-04	30	75																									
		80-05	30	80																									
		80-06	30	80																									
		110-04	30	80																									
	110-06	30	80																										
	110-08	30	80																										
	AITTJ	110-10	20	55																									
		110-15	20	45																									
	AITTJ60	110-03	20	25																									
		110-04	20	35																									
		110-05	20	40																									
		110-06	20	40																									
		110-08	20	55																									
		110-10	20	55																									
	AIXR	110-03	15	30																									
		110-04	15	60																									
		110-05	15	60																									
		110-06	15	60																									
		110-08	15	70																									
APTJ	110-02	20	90																										
	110-025	20	90																										
	110-03	20	90																										
	110-04	20	85																										
	110-05	20	90																										
	110-06	20	90																										
	110-08	20	85																										

For PWM Systems:

- NOZZLE Designed for use with PWM systems
- NOZZLE Use with John Deere ExactApply™ system ONLY

Coverage guide (factor of type, size and/or pressure range):

- Provides best balance of coverage and drift control
- Provides additional drift control by creating larger droplets
- No classification

Manufacturer	Nozzle Type	Size	Pressure		Pressure Range (PSI)																						
			Min	Max	10	15	20	25	30	35	40	45	50	55	60	65	70	75	80	85	90	95	100	105	110	115	120
TeeJet	TTI	110-02	15	65																							
		110-025	15	70																							
		110-03	15	65																							
		110-04	15	85																							
		110-05	15	65																							
		110-06	15	55																							
		110-08	15	55																							
		110-10	15	55																							
	TTI60	11003	15	65																							
		11004	15	60																							
		11005	15	55																							
		11006	15	50																							
		11008	15	50																							
Wilger	MR	110-04	25	35																							
		110-05	25	35																							
		110-06	25	60																							
		110-08	25	60																							
		110-10	25	50																							
		110-125	25	70																							
	DR	110-03	30	50																							
		110-04	30	50																							
		110-05	30	70																							
		110-06	30	70																							
		110-08	30	60																							
		110-10	30	100																							
	UR	110-03	30	90																							
		110-04	30	100																							
		110-05	30	100																							
		110-06	30	100																							
		110-08	30	90																							
		110-10	30	100																							

All qualified nozzle and pressure combinations for Enlist® herbicides are listed on [Enlist.com/nozzles](https://www.enlist.com/nozzles)



Information here is general guidance and not an endorsement or recommendation from Corteva AgriScience. Consult nozzle manufacturer or your advisor on nozzle and pressure selection. Minimum pressures are not recommended to achieve optimal coverage for weed control.



Visit us at [Enlist.com](https://www.enlist.com)

®/™ Trademarks of Corteva Agriscience and its affiliated companies. Enlist Duo® herbicide is not registered for sale or use in all states or counties. Contact your state pesticide regulatory agency to determine if a product is registered for sale or use in your area. Enlist One herbicide is the only 2,4-D product authorized for use in Enlist crops. Always read and follow label directions. ExactApply is a trademark of Deere & Co. ©2023 Corteva. 013707-2 COR (12/23)

